

Product Bulletin No.: 2016PB005C

14-Feb-2019 FlexPS Product Retirement Bulletin

14-Mar-2024

Update

Senstar herein announces the immediate complete end-of-life of the FlexPS fence-mounted perimeter intrusion detection system.

FlexPS Product Retirement

Senstar's FlexPS fence sensor has a long history of providing reliable protection to critical infrastructure sites all over the world. However given the availability of newer and better performing alternatives, Senstar has established the following product retirement timeline for the FlexPS product line:

Date	Milestone
14-Feb-2019	Product Retirement Bulletin issued (this document), affected products are still available for new sales.
30-June-2019	Product no longer available for new sales. Product available only for the purpose of replacing an existing unit that is beyond economic repair.
31-Dec-2022	Repair services transition to a Reasonable Effort basis. Repair will be performed when it is technically and financially practical.
14-Mar-2024	Complete end of life – all repair services discontinued

Affected part numbers

The affected part numbers are given in Table 1 below.

Product Migration

For further information For customers wishing to upgrade to a new fence sensor Senstar recommends either the FlexZone ranging fence intrusion detection system, the FiberPatrol FP1150 ranging fiber-optic fence detection system, FP400 zone-based fiberoptic fence detection system, or the Senstar LM100 combination fence sensor and intelligent lighting system.

Please direct inquiries or requests for quotation to your local Senstar representative – see www.senstar.com for contact and product information.

Stewart Dewar **Product Manager** Senstar Corporation

O: +1-613-839-5572, x4344 E: stewart.dewar@senstar.com

Stewart Deware

2016PB005C Page 1

Part Number	Description
	Bundles
G5FG0401	FlexPS two-zone kit - 100 m (328 ft.) protects up to 90 m (295 ft.) of chain link fence
G5FG0402	FlexPS two-zone kit - 200 m (656 ft.) protects up to 180 m (590 ft.) of chain link fence
G5FG0403	FlexPS two-zone kit - 300 m (984 ft.) protects up to 270 m (885 ft.) of chain link fence
	Processors
G5EM0101	FlexPS processor in NEMA 4 aluminum enclosure
	Processor Options
G5KT0200	FlexPS enclosure pole-mounting kit (2 brackets, 2 clamps 1 7/8" to 5")
G5KT0400	FlexPS enclosure locking kit
GE0499	FlexPS back up battery, 6V 1.4Ah, sealed lead acid
	Cable & Accessories
G5FG0203	MEX sensor cable on 300m (984 ft.) roll. Terminations and cable ties sold separately
G5FG0501	MEX sensor cable on 100m (328 ft.) roll. Includes 333 UV resistant caties. Terminations sold separately
G5FG0503	MEX sensor cable on 300m (984 ft.) roll. Includes 1000 UV resistant cable ties. Terminations sold separately
C6KT2600	Cable splice and terminator kit.
G5FG0300	ArmourFLEX vandal resistant 3/8" flexible aluminum conduit with factory-installed MEX cable. 100m (328 ft.) roll
C6KT0900	ArmourFLEX condulet fittings, one kit required per splice and termina kit.
C6FG0902	Mark 2 sensor cable for FlexPS/Intelli-FLEX. 150m (500') roll.
C6SP1300	ArmourFLEX vandal resistant aluminum flex conduit with factory installed Intelli-FLEX Mark 2 sensor cable. Supplied in 100m (330') ronly.
82-210000	Telescoping Sensor cable retractor for sliding gates - Telegate - includ Instruction Sheet.
C6EM0301	Gate bypass module, locally activated by key switch
C6EM0400	Gate bypass module, for remote activation.
G5SP0202	Non-sensitive lead-in cable for MEX sensor cable, 150m (492 ft.) roll

2016PB005C Page 2

Table 1 – Part Numbers Affected by FlexPS Retirement Bulletin		
G5SP0201	Non-sensitive lead-in cable for MEX sensor cable, 30m (98 ft.) roll	
	Spares	
G5EM0200	FlexPS circuit card assembly on mounting plate	
G5KT0302	FlexPS circuit card on adaptor plate for mounting into Intelli-FLEX enclosure	
G5KT0301	FlexPS circuit card on adaptor plate for mounting into FPS enclosure	
G5DA0120	FlexPS product documentation - CD	

2016PB005C Page 3