

FiberPatrol® Outdoor Splice Enclosure

GM0749-24, GM0749-48

The outdoor splice enclosure holds up to two (GM0749-24) or four (GM0749-48) splice trays. The splice enclosure is waterproof and can be mounted on a fence, directly buried or placed in a protective vault.

Specifications

- Size (L/W/H):
 - GM0749-24: 37.5 x 21.6 x 7.6 cm (14.75 x 8.5 x 3 in)
 - GM0749-48: 37.5 x 21.6 x 12.1 cm (14.75 x 8.5 x 4.25 in)
- Weight: Aprox. 1.8 kg (4.0 lbs)
- Cable entrance ports: two 19 mm (3/4 in), one 25 mm (1 in)
- Splice tray support:
 - GM0749-24: Up to 2 splice trays (24 splices total)
 - GM0749-48: Up to 4 splice trays (48 splices total)
- Includes sealing system
- Mechanical protection and environmental sealing conform to Telcordia GR-771-CORE standard for an Environmentally Sealed Closure
- Ingress protection equivalent to IP68
- Included accessories:
 - Port sealing plugs: one for 19 mm (3/4 in) cable port, one for 25 mm (1 in) cable port
 - Four (4) fiber retainer clips
 - Two (2) bond brackets for grounding metallic armor
 - One (1) roll of LOCK-TAPE sealing tape
 - Four (4) lengths of transport tubing
 - One (1) length of emery cloth
 - One (1) cable measuring tape



Port sealing plugs



Bond bracket



Fiber retainer clip



Transport tubing



Emery cloth



LOCK-TAPE sealing tape



Measuring tape



Splice enclosure cover (left) and base (right)

